



**FLEET (LINE MARKERS) LTD**  
Fleet House  
Spring Lane  
Malvern  
Worcestershire  
WR14 1AT  
U.K.  
Tel: +44 (0) 1684 573 535  
Fax: +44 (0) 1684 892 784

## PRODUCT HEALTH AND SAFETY

### 1. COMPANY PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **EASIFLO**  
PRODUCT PURPOSE: **DRY LINE MARKING (OUTDOOR)**  
COMPANY IDENTIFICATION: **FLEET (LINE MARKERS) LTD.**  
Fleet House, Spring Lane,  
Spring Lane Industrial Estate,  
Malvern, Worcs.  
WR14 1AT  
TEL: +44(0) 1684 573535  
FAX: +44(0) 1684 892784  
E-MAIL: sales@fleetlinemarkers.com  
**EMERGENCY TELEPHONE +44(0) 1684 573535**

### 2. HAZARD IDENTIFICATION

PRIMARY ROUTES OF EXPOSURE: Dust Inhalation  
Eye Contact  
Skin Contact  
INHALATION: Prolonged exposure to limestone dust may cause respiratory problems.  
EYE CONTACT: Direct contact with this material may cause irritation.  
SKIN CONTACT: Prolonged or repeated contact may cause dryness of the skin and irritation.

### 3. COMPOSITION

Calcium Carbonate (Limestone) powder.

### 4. FIRST AID MEASURES

INHALATION; EYE CONTACT: Remove to fresh air.  
Flush eyes with large amounts of water.  
Seek medical advice if irritation persists.  
SKIN CONTACT: Wash with soap and water.  
INGESTION: Non-toxic, non-corrosive.

### 5. FIRE FIGHTING MEASURES

Not flammable.

### 6. ACCIDENTAL RELEASE MEASURES

Avoid creating dust. Collect by vacuum cleaning, or hose away with plenty of water.

### 7. HANDLING AND STORAGE

HANDLING: Use appropriate controls to avoid creating dust.  
STORAGE: Store in a dry covered area. Do not store near acids.

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

EXPOSURE CONTROLS: Ensure occupational exposure limits are maintained.  
(Long term exposure limit for total inhalable dust  
10mg/m<sup>3</sup>, 8h TWA and respirable dust 4mg/m<sup>3</sup>, 8h TWA  
- UK EH40/99)

PERSONAL PROTECTION: Respiratory: Wear appropriate safety dust mask if conditions are dusty.

Hand: Gloves, if risk of skin contact.

1 of 3





**FLEET (LINE MARKERS) LTD**  
Fleet House  
Spring Lane  
Malvern  
Worcestershire  
WR14 1AT  
U.K.  
Tel: +44 (0) 1684 573 535  
Fax: +44 (0) 1684 892 784

## PRODUCT HEALTH AND SAFETY

Eye: Wear safety glasses. Provide eyewash.  
Skin: Standard industrial overalls.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Off-white powder.  
Odour: None  
pH: 8.5 - 9.5  
Boiling point: N/A  
Specific Gravity: 2.6 - 2.8  
Water solubility: Virtually insoluble

### 10. STABILITY AND REACTIVITY

**Easiflo** is stable under normal conditions of use - also see Handling and Storage.  
Materials to avoid: Acids. Reacts with acids forming carbon dioxide.

### 11. TOXICOLOGICAL INFORMATION

This product is regarded as non-toxic.

### 12. ECOLOGICAL INFORMATION

Not biodegradable, inert.

### 13. DISPOSAL INFORMATION

**Easiflo** is not classified as hazardous waste. This product can be disposed of as non-toxic waste in approved sites in accordance with local regulations.

### 14. TRANSPORT INFORMATION

**Easiflo** is not classified as hazardous for transportation.

### 15. REGULATORY INFORMATION

Classification and Labelling: Complies with EEC Directives, U.K. EH40 and COSHH guidelines.

### 16. OTHER INFORMATION

Fleet (Line Markers) Ltd. classifies this product as non-hazardous or toxic under normal conditions of use. The information provided in this Safety Data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be carried out and should not be construed as a guarantee of specific properties.

Date of issue: January 19<sup>th</sup> 2009

Revision Reference: 004

